

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

This Safety Data Sheet adheres to the standards and regulatory requirements of Australia and may not meet the regulatory requirements in other countries.

SECTION 1: IDENTIFICATION1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BIFLEX AQUAMAX

Other means of identification : BIFENTHRIN 100 G/L SC

Recommended use of the chemical and restrictions on use

Recommended use : Termiticide and insecticide

Restrictions on use : Use as recommended by the label.

Manufacturer or supplier's details

Company : FMC Australasia Pty Ltd

Address : Building B, Suite G.01, 12 Julius Avenue
North Ryde NSW 2113
Australia

Telephone : 1 800 066 355

Telefax : (02) 9923 6011

E-mail address : SDS-Info@fmc.com

Emergency telephone number : For leak, fire, spill or accident emergencies, call:
1800 033 111 (Ixon)

Medical emergency:
1 800 033 111 (Transport and 24 h Medical information)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity - : Category 2 (Central nervous system)

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

single exposure

Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system)

GHS label elements

Hazard pictograms :

Signal word : Warning

Hazard statements : H302 + H332 Harmful if swallowed or if inhaled.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H371 May cause damage to organs (Central nervous system).
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

disposal plant.

Other hazards which do not result in classification

Very toxic to aquatic life with long lasting effects.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
bifenthrin (ISO)	82657-04-3	≥ 1 - < 10
propane-1,2-diol	57-55-6	< 10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- General Symptoms : Exposure may result in neurotoxicity with symptoms including tremors, impaired gait, and excessive salivation. Tremors may disappear with continued exposure.
- Causes serious eye irritation.
Exposure to skin may result in mild symptoms include itching,

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version 1.3	Revision Date: 21.08.2026	SDS Number: 50001562	Date of last issue: 02.08.2021 Date of first issue: 30.07.2021
----------------	------------------------------	-------------------------	---

hives or rash, and skin redness. More severe symptoms include sneezing, itchy watery eyes, and difficulty breathing. May cause damage to organs.

Symptoms After Inhalation : None known.

Symptoms After Skin Contact : None known.

Symptoms After Eye Contact : None known.

Symptoms After Swallowing : None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
Foam

Unsuitable extinguishing media : High volume water jet
Do not spread spilled material with high-pressure water streams.

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Thermal decomposition can lead to release of irritating gases and vapours.
Halogenated compounds
Carbon oxides

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Hazchem Code : •3Z

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures : Use personal protective equipment.
Sweep up to prevent slipping hazard.

SAFETY DATA SHEET



BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue:
1.3	21.08.2026	50001562	02.08.2021
			Date of first issue: 30.07.2021

gency procedures

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propane-1,2-diol	57-55-6	TWA (partic-	10 mg/m3	AU OEL

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version 1.3 Revision Date: 21.08.2026 SDS Number: 50001562 Date of last issue: 02.08.2021
Date of first issue: 30.07.2021

		ulate)		
		TWA (Total (vapour and particles))	150 ppm 474 mg/m ³	AU OEL

Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate, butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Always have on hand a first-aid kit, together with proper instructions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid
Form : liquid
Colour : white, opaque
Odour : mild, like soap
pH : not determined
Melting point/ range : not determined
Boiling point/boiling range : not determined
Flash point : Not determined, but expected to be > 100°C
Flammability (liquids) : Not expected to be ignitable
Self-ignition : does not ignite
Relative density : 1.02
Bulk density : not determined
Solubility(ies)
Water solubility : not determined
Viscosity
Viscosity, kinematic : not determined
Explosive properties : Not explosive
Oxidizing properties : Non-oxidizing

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	Protect from frost, heat and sunlight.
Incompatible materials	:	Strong oxidizing agents Strong acids Strong bases
Hazardous decomposition products	:	Stable under recommended storage conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity	:	LD50 (Rat, male and female): 531 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat, male and female): 4.94 mg/l Exposure time: 4 Hour Test atmosphere: dust/mist Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Remarks: Based on data from similar materials

Components:

bifenthrin (ISO):

Acute oral toxicity	:	LD50 (Rat, male and female): 56.7 mg/kg Symptoms: Convulsions, Tremors, ataxia LD50 (Mouse, female): 42.5 mg/kg Method: OPPTS 870.1100
Acute inhalation toxicity	:	LC50 (Rat, female): 0.6 - 1.2 mg/l Exposure time: 4 Hour Test atmosphere: dust/mist Method: OECD Test Guideline 403 Symptoms: Tremors, Convulsions LC50 (Rat, male): 1.10 mg/l Exposure time: 4 Hour Test atmosphere: dust/mist Method: OECD Test Guideline 403 Symptoms: Tremors, Fatality

SAFETY DATA SHEET



BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Remarks: no mortality

propane-1,2-diol:

Acute oral toxicity : LD50 (Rat, male and female): 22,000 mg/kg

Acute inhalation toxicity : LC0 (Rabbit): 31.7 mg/l
Exposure time: 2 Hour
Test atmosphere: vapour
Remarks: no mortality

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Components:

bifenthrin (ISO):

Species : Rabbit
Method : OECD Test Guideline 404
Result : slight or no skin irritation.
GLP : yes

propane-1,2-diol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result : Eye irritation

Components:

bifenthrin (ISO):

Species : Rabbit
Result : Slight or no eye irritation
Method : OECD Test Guideline 405
GLP : yes

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

propane-1,2-diol:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Species	:	Guinea pig
Result	:	May cause sensitisation by skin contact.
Remarks	:	Based on data from similar materials
Remarks	:	Causes sensitisation.

Components:

bifenthrin (ISO):

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	May cause sensitisation by skin contact.
GLP	:	yes

propane-1,2-diol:

Test Type	:	Maximisation Type
Species	:	Guinea pig
Result	:	negative

Chronic toxicity

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

bifenthrin (ISO):

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative
	:	Test Type: gene mutation test Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476

SAFETY DATA SHEET



BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

Result: negative

GLP: yes

Test Type: Mouse lymphoma assay

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo

: Test Type: Sex-linked Recessive Lethal Test
Species: Drosophila melanogaster (vinegar fly)
Result: negative

Test Type: unscheduled DNA synthesis assay

Species: Rat

Method: OECD Test Guideline 486

Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse (male and female)

Method: OECD Test Guideline 474

Result: negative

propane-1,2-diol:

Genotoxicity in vitro

: Test Type: reverse mutation assay
Result: negative

Genotoxicity in vivo

: Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Carcinogenicity

Based on available data, the classification criteria are not met.

Components:

bifenthrin (ISO):

Species	: Rat, female
Application Route	: Oral
Exposure time	: 2 Years
NOAEL	: 3 mg/kg bw/day
Result	: negative

Species	: Mouse, male
Application Route	: Oral
Exposure time	: 18 month(s)
NOAEL	: 7.6 mg/kg bw/day
Result	: positive
Symptoms	: malignant tumors

propane-1,2-diol:

Species	: Rat
Application Route	: Oral
Exposure time	: 2 Years

BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue:
1.3	21.08.2026	50001562	02.08.2021
			Date of first issue: 30.07.2021

Result : negative

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:**bifenthrin (ISO):**

Effects on fertility : Test Type: Two-generation study
Species: Rat
Application Route: Oral
General Toxicity - Parent: NOAEL: 3 mg/kg bw/day
General Toxicity F1: NOAEL: 5 mg/kg bw/day
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Oral
General Toxicity Maternal: NOAEL: 2.7 mg/kg bw/day
Teratogenicity: NOAEL: 2.7 mg/kg bw/day
Symptoms: Maternal effects
Result: No teratogenic effects

Test Type: Embryo-foetal development
Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 1 mg/kg bw/day
Teratogenicity: NOAEL: 2 mg/kg bw/day
Result: No teratogenic effects

Species: Rat
Application Route: Oral
General Toxicity Maternal: LOAEL: 7.2 mg/kg bw/day
Developmental Toxicity: LOAEL: 7.2 mg/kg bw/day
Embryo-foetal toxicity: NOEL: 9.0 mg/kg bw/day
Method: OECD Test Guideline 426
Result: Animal testing did not show any effects on fertility.,
Some evidence of adverse effects on development, based on animal experiments.

propane-1,2-diol:

Effects on fertility : Test Type: reproductive and developmental toxicity study
Species: Mouse
Application Route: Oral
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 414
Result: Animal testing did not show any effects on fertility.
Remarks: Based on data from similar materials

BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

STOT - single exposure

May cause damage to organs (Central nervous system).

Components:**bifenthrin (ISO):**

Target Organs	: Central nervous system
Assessment	: Causes damage to organs.

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:**bifenthrin (ISO):**

Target Organs	: Central nervous system
Assessment	: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Repeated dose toxicity**Components:****bifenthrin (ISO):**

Species	: Rat, male and female
NOEL	: 100 ppm
Application Route	: Oral - feed
Exposure time	: 90 d
Remarks	: No toxicologically significant effects were found.

Species	: Dog, male and female
NOEL	: 2.5 mg/kg bw/day
Application Route	: Oral - feed
Exposure time	: 13 w
Symptoms	: Tremors

Species	: Dog, male and female
NOEL	: 1.5 mg/kg
Application Route	: Oral
Exposure time	: 52 w
Dose	: 0.75, 1.5, 3, 5 mg/kg bw/day
GLP	: yes
Symptoms	: Tremors

propane-1,2-diol:

Species	: Rat, male and female
NOAEL	: 1,700 mg/kg
Application Route	: Oral
Exposure time	: 2 Years

Species	: Rat, male and female
NOAEL	: 1,000 mg/kg
LOAEL	: 160 mg/kg

SAFETY DATA SHEET



BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

Application Route : Inhalation
Exposure time : 90 Days

Aspiration toxicity

Based on available data, the classification criteria are not met.

Components:

bifenthrin (ISO):

The substance does not have properties associated with aspiration hazard potential.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bifenthrin (ISO):

Toxicity to fish	: LC50 (Salmo gairdneri): 0.00015 mg/l Exposure time: 96 Hour Test Type: flow-through test LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.00035 mg/l Exposure time: 96 Hour Test Type: flow-through test LC50 (Oncorhynchus mykiss (rainbow trout)): 0.000256 mg/l Exposure time: 96 Hour Test Type: semi-static test Method: OECD Test Guideline 203 GLP: yes LC50 (Pimephales promelas (fathead minnow)): 0.000234 mg/l Exposure time: 96 Hour Test Type: semi-static test Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia (water flea)): 0.00011 mg/l Exposure time: 48 Hour LC50 (Daphnia (water flea)): 0.0016 mg/l Exposure time: 48 Hour
Toxicity to algae/aquatic	: EC50 (algae): 0.822 mg/l

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

plants Exposure time: 72 Hour

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.00012 mg/l
Exposure time: 21 Day

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.0013 µg/l
Exposure time: 21 Day

NOEC (Daphnia magna (Water flea)): 0.00095 µg/l
Exposure time: 21 Day

Toxicity to soil dwelling organisms : LD50 (Eisenia fetida (earthworms)): > 16 mg/kg
Exposure time: 14 Day

Toxicity to terrestrial organisms : LD50 (Colinus virginianus (Bobwhite quail)): 1,800 mg/kg

LD50 (Anas platyrhynchos (Mallard duck)): > 2,150 mg/kg

LD50 (Apis mellifera (bees)): 0.07 µg a.i./bee
Exposure time: 48 Hour
End point: Acute oral toxicity
Method: OECD Test Guideline 213

LD50 (Apis mellifera (bees)): 0.0201 µg a.i./bee
Exposure time: 48 Hour
End point: Acute contact toxicity
Method: OECD Test Guideline 214

ED50 (Apis mellifera (bees)): 143 ng ai larva
Exposure time: 7 Day
End point: Acute larval toxicity
Method: OECD 237

ED50 (Apis mellifera (bees)): 15.15 ng ai larva/day
Exposure time: 22 Day
End point: Chronic larval toxicity
Method: OECD 239

NOAEL (Apis mellifera (bees)): 2.30 ng ai larva/day
Exposure time: 22 Day
End point: Chronic larval toxicity
Method: OECD 239

ED50 (Apis mellifera (bees)): 300 ng a.i./bee/day
Exposure time: 10 Day
End point: Chronic oral toxicity
Method: OECD TG 245

NOAEL (Apis mellifera (bees)): 170 ng a.i./bee/day
Exposure time: 10 Day
End point: Chronic oral toxicity
Method: OECD TG 245

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

propane-1,2-diol:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l Exposure time: 96 Hour
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Mysidopsis bahia (opossum shrimp)): 18,800 mg/l Exposure time: 96 Hour
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 34,100 mg/l Exposure time: 48 Hour Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 13,020 mg/l Exposure time: 7 Day
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): > 20,000 mg/l Exposure time: 18 Hour

Persistence and degradability

Components:

bifenthrin (ISO):

Biodegradability	:	Result: Not readily biodegradable.
Stability in water	:	Degradation half life (DT50): 2.2 Day Hydrolysis: at 60 °C Degradation half life (DT50): 15.6 Day Hydrolysis: at 40 °C

propane-1,2-diol:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 23.6 % Exposure time: 64 Day Method: OECD Test Guideline 306
------------------	---	--

Bioaccumulative potential

Components:

bifenthrin (ISO):

Bioaccumulation	:	Species: Lepomis macrochirus (Bluegill sunfish) Bioconcentration factor (BCF): 1,709 Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is possible.
Partition coefficient: n-octanol/water	:	log Pow: 6.6

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version 1.3	Revision Date: 21.08.2026	SDS Number: 50001562	Date of last issue: 02.08.2021 Date of first issue: 30.07.2021
----------------	------------------------------	-------------------------	---

propane-1,2-diol:

Partition coefficient: n-octanol/water : log Pow: -1.07

Mobility in soil

Components:

bifenthrin (ISO):

Distribution among environmental compartments : Koc: 236610 ml/g, log Koc: 5.37
Remarks: immobile

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bifenthrin)
Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (Bifen-

SAFETY DATA SHEET



BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

thrins)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bifenthrin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes
Remarks : Environmentally hazardous substances/Marine Pollutants in single or combination packaging containing a net quantity per single or inner packaging of 5 kg or less for solids, or having a net quantity per single or inner packaging of 5 L or less for liquids may be transported as non-dangerous goods as provided in special provision A197 of the IATA and section 2.10.2.7 of IMDG code.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bifenthrin)
Class : 9
Packing group : III
Labels : 9
Hazchem Code : •3Z
Environmentally hazardous : yes
Remarks : Environmentally hazardous substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the ADG Code when transported by road or rail in packagings that do not incorporate a receptacle exceeding 500 kg / liters, or IBCs

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

BIFLEX AQUAMAX



Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2021
1.3	21.08.2026	50001562	Date of first issue: 30.07.2021

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons Standard) Instrument : Schedule 6

APVMA no.: 60678
Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

The components of this product are reported in the following inventories:

TW TCSI	: On the inventory, or in compliance with the inventory
US TSCA	: Product contains substance(s) not listed on TSCA inventory.
AU AIIC	: Not in compliance with the inventory
CA. DSL	: This product contains the following components that are not on the Canadian DSL nor NDSL. 2-METHYLBIPHENYL-3-YLMETHYL (Z)-(1RS,3RS)-3-(2-CHLORO-3,3,3-TRIFLUOROPROP-1-ENYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE Smectite-group minerals
JP ENCS	: Not in compliance with the inventory
JP ISHL	: Not in compliance with the inventory
KR KECI	: On the inventory, or in compliance with the inventory
PH PICCS	: Not in compliance with the inventory
CN IECSC	: On the inventory, or in compliance with the inventory
NZ NZIoC	: Not in compliance with the inventory

SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision Date : 21.08.2026
Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

SAFETY DATA SHEET



BIFLEX AQUAMAX

Version	Revision Date:	SDS Number:	Date of last issue:
1.3	21.08.2026	50001562	02.08.2021
			Date of first issue: 30.07.2021

AU OEL / TWA : Exposure standard - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

AU / 6N